

External air hand tool

PENWELD S



- Robust and simple construction
- Short and light for longer working periods
- Recessed rotary knob against accidental adjustment
- High quality, sturdy hose











Technical data

Voltage	V~	120 V; 230
Frequency	Hz	50 / 60
Power	W	1000 – 1550
Temperature	°C	60 – 600
Temperature setting stepless		Yes
Display		No
Outdoor use		Yes
Nozzle connection (∅)		31.5 mm; M14
Size (L × ∅)	mm	254.0 – 275.0 × 54, handle ∅ 37
Conformity mark		CE UK
Protection class II		□

Article No.:

173.372	PENWELD 305-S, 230 V / 1000 W, 3 m, M14, EU plug
173.373	PENWELD 305-S, 230 V / 1000 W, 3 m, M14, CH plug
173.374	PENWELD 305-S, 120 V / 1000 W, 3 m, M14, US plug
173.375	PENWELD 305-S, 230 V / 1000 W, 8 m, M14, EU plug
173.378	PENWELD 500-S, 230 V / 1550 W, 3 m, EU plug
173.379	PENWELD 500-S, 120 V / 1550 W, 3 m, US plug
177.345	PENWELD 500-S, 230 V / 1550 W, 3 m, CN plug

Accessories PENWELD S

	105.622 ∅ 5 mm tubular nozzle, 15° screw-on
	106.988 Tacking nozzle, screw-on
	113.666 ∅ 3 mm round drawing nozzle with tacking tip, screw-on 113.399 ∅ 4 mm round drawing nozzle, with tacking tip, screw-on
	113.876 ∅ 3 mm round drawing nozzle without tacking tip, screw-on 113.874 ∅ 4 mm round drawing nozzle, without tacking tip, screw-on
	113.670 Triangular drawing nozzle with tacking tip, screw-on, 5.7 mm, profile A 113.877 without tacking tip, screw-on 5.7 mm, profile A 106.986 without tacking tip, screw-on 7 mm, profile B 106.987 without tacking tip, screw-on 7 × 5.5 mm
	126.552 ∅ 4 mm drawing nozzle, screw-on for floor plastics
	Angular adapter for screw-on nozzles, screw-on 127.726 30° 127.727 45°
	170.881 Tool stand PENWELD
	172.330 One-touch fitting G3/8" 172.333 One-touch fitting G1/2"
	172.331 Coupler plug ∅ 14 mm